



- CLOSER: SHALL BE HEAVY USAGE, DOOR SAVER TYPE WITH A 10 YEAR GUARANTEE (CORRIDOR SIDE)
- VIEW WINDOW: SHALL BE 1/4" LEXAN® OR EQUAL.
- DOOR: SHALL BE 1 3/4" SOLID CORE DOOR LAMINATED PLASTIC ON BOTH SIDES (DOOR EDGES TO RECEIVE EDGE BANDING TO MATCH FACE OF DOOR).
- PUSH PLATE: SHALL BE 15" X 3-1/2" X 1/8" (CORRIDOR SIDE)
- PULL-RING: SHALL BE HEAVY DUTY, FLUSH MOUNTED TYPE WITH STAINLESS STEEL FINISH (COURT SIDE)
- FRAME: SHALL CONSTRUCTED FROM 1-1/8" THICK HIGH DENSITY LAMINATED PANEL MATERIAL. STOPS SHALL BE CONSTRUCTED OF 7/8" THICK HIGH DENSITY LAMINATED PANELS IN MATCHING COLOR.
- HINGE: SHALL BE FULL LENGTH PIANO TYPE MILL FINISH WITH 1/4" STEEL PIN.
- THRESHOLD: SHALL BE 1" THICK SOLID NORTHERN HARD MAPLE WITH TWO COATS OF POLYURETHANE FINISH.

PRODUCT: (RIGHT-HAND SWING IS STANDARD). UNITS SHALL BE COMPLETELY PRE-HUNG, FINISHED WITH ALL NECESSARY HARDWARE ATTACHED, PROPERLY PACKAGED, AND READY FOR INSTALLATION.

COMPONENTS: FRAME SHALL BE 1-1/8" X 6-1/8" OF HIGH DENSITY PANEL MATERIAL, PRE-FINISHED WHITE. THRESHOLD SHALL BE 1" THICK SOLID NORTHERN HARD MAPLE WITH TWO COATS OF POLYURETHANE FINISH.

HARDWARE: HINGE SHALL BE FULL LENGTH PIANO TYPE AND DOOR STOPS PRE-MOUNTED TO WOOD FRAME. HARDWARE ON OUTSIDE OF DOOR TO CONSIST OF CLOSER AND PUSH PLATE. HARDWARE ON INSIDE OF DOOR TO CONSIST OF PULL-RING FLUSH WITH THE INSIDE OF THE COURT DOOR SURFACE. THE VIEW WINDOW IS FINISHED AND FLUSH WITH THE INSIDE OF THE COURT DOOR SURFACE.

INSTALLATION: COURT SIDE OF THE DOOR UNIT TO BE FLUSH WITH THE COURT PLAYING SURFACE.

ALSO AVAILABLE:

- CUSTOM SIZES
- LEFT-HAND SWING DOOR

NOTE: DOOR CLEARANCE IS 1/8" AT JAMBS AND HEAD, AND 3/8" AT THRESHOLD.

UNITS ARE INDIVIDUALLY CRATED FOR SHIPMENT.

THESE DOORS ARE FOR INTERIOR USE ONLY

MANUFACTURER RESERVES THE RIGHT TO MODIFY THEIR PRODUCT FOR IMPROVEMENT OR AS DEEMED NECESSARY.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

OUTSIDE FRAME DIMENSIONS

40-5/8" x 82-1/4"